

# **Instructions for Use**

Minor Procedure Table, Phenolic 800-0026

Minor Procedure Table, Carbon Fiber 800-0027

Replacement Pad
Deluxe Foam Pad (Minor) 508-1432


# **Copyright Notice**

All rights reserved. Any duplication, adaption or translation without prior written consent is prohibited unless otherwise provided for in relevant copyright laws



**Initial Release**: 1/25/2012





EC REP Authorized Representative

Emergo Europe, Prinsessegracht 20, 2514 AP The Hague, The Netherlands

# **GENERAL SPECIFICATIONS**

Device Dimensions (maximum)


- Patient Weight Capacity: 600 lbs. (20 lbs. @ far end of table, 41 lbs. in center of table)
- Length: 30" +/- 0.5"
- Width: 15" +/- 0.5"
- *Maximum Raised Height: 3.5" +/- 0.5"*
- Phenolic Depth: .375" +/- 0.5"
- Carbon Fiber Depth: .25" +/- 0.5"
- Phenolic: Device Weight: 10 +/- 0.5 lbs.
- Carbon Fiber: Device Weight: 9 +/- 0.5 lbs.
- Hand Table Mounting Post: 6"L
- Attaches to rail of surgical table at any point on rail
- Single-person installation


## **INTENDED USE**


Its function is to provide a stable platform for all arm and hand surgeries.

#### INSTRUCTIONS

Become familiar with patient positioning device's features before use with patient. Always practice on a nurse, physician or appropriate volunteer prior to using clinically.







- 1. Attach Deluxe Rail Clamps to side rail and place them approximately 1' apart (as shown)
- 2. *Insert mounting rods into clamps (as shown)*
- 3. Adjust procedure table so that it is level with surgical table pad. Secure table to accessory rail using the Locking Knobs of the clamps (as shown)
- 4. Includes 1" pressure management pad
- 5. Clamps sold separately

#### COMPONENT OVERVIEW

Rectangle Minor Procedure Table, Phenolic or Carbon Fiber are surgical table extensions that attach to all rails

# Replacement Pad: 508-1432 Deluxe Foam Pad (Minor)

## **Deluxe Rail Clamps for use (2 required)**

- US: 0.374" x 1.122" (9.5 mm x 28.5 mm) PN# 800-0248
- Denyer: 0.236" x 1.496" (6 mm x 38 mm) PN# 800-0248-DEN
- Europe: 0.394" x 0.984" (10 mm x 25 mm) PN# 800-0248-EU
- Eschmann (UK): 0.236" x 1.260" (6 mm x 32 mm) PN# 800-0248-UK
- Japan: 0.354" x 1.260" (9 mm x 32 mm) PN# 800-0248-JPN
- Swiss: 0.394" x 1.181" (10 mm x 30 mm ) PN# 800-0248-SWISS

# **GENERAL INFORMATION**

- Product not made with Natural Rubber Latex
- Device supports 600 lb. proportional patient load (6'4" tall patient per 99% human body model)
- Product warranty covers product from manufacturing defects for period of 2 years
- If damaged in shipping, call Customer Service at (888) 724-8763 or (781) 982-7000 to obtain Return Material Authorization number. For product warranty issues, contact Customer Service.
- Product is maintenance-free, check product condition before next use
- Life of device is 3 years under normal use
- Store device between -4°F to +86°F

## **DISPOSAL**

- General Prevent infection by cleaning and disinfecting product before disposal
- Packaging Dispose packaging material via household waste according to national requirements
- SchureMed accepts back used or retired products or dispose of product in accordance with national requirements



# **Product Use Warnings**

## WARNING!

WARNING! Maximum load should not exceed appropriate proportion of a patient weighing 600 lbs. Use care with low-maximum load capacity surgical tables that accessory rails are not overloaded.



#### WARNING!

Hazard resulting from incorrect use. Strictly follow Instructions for Use with your Operating Table system.

## **CLEANING RECOMMENDATION**

Follow current Association of periOperative Registered Nurses Journal Guidelines for proper cleaning and disinfection procedures.



## WARNING!

Adhere to standards for blood-borne pathogens from the Occupational Safety and Health Administration. Use recommended protective clothing, gloves, masks and eye protection to clean accessory.

## **CAUTION**

Strictly read/follow manufacturer's directions for cleaning fluids. DO NOT use cleaners containing phenolics.

- 1. Remove major contaminants from accessory with disposable materials. Follow appropriate biohazard waste disposal procedures.
- 2. Apply cleaning fluid liberally to entire accessory and wipe with clean, lint-free cloth until all moisture and cleaning fluid is removed from accessory
- 3. Let accessory dry



## **Symbol Explanation**



Date of Manufacture





**LOT** Batch Code/Serial Number



IFU-800-0026 REV 3.02 IFU-800-0027 REV 3.02