

tri mode
new!



P-2420

OVERALL SIZE

30"W x 21¼"D x 25¼"H

COMPARTMENT SIZE

- 4.75 cubic ft.
- 26½"W x 17"D x 18¼"H

• **tri mode Range:**

- Irrigation: 90°F - 150°F
- Injection: 90°F - 104°F
- Blanket: 90°F - 160°F

• **Total Capacity:**

- 20 1-liter bags or
- 24 1-liter bottles
- 9 - 12 blankets

• Data Logger (Option)

• Caster (Option)

tri mode
new!



P-2430

OVERALL SIZE

30"W x 27½"D x 25¼"H

COMPARTMENT SIZE

- 5.5 cubic ft.
- 26½"W x 19¾"D x 18¼"H

• **tri mode Range:**

- Irrigation: 90°F - 150°F
- Injection: 90°F - 104°F
- Blanket: 90°F - 160°F

• **Total Capacity:**

- 30 1-liter bags or
- 48 1-liter bottles
- 10 - 14 blankets

• Data Logger (Option)

• Caster (Option)

warming cabinets

blanket & fluid

features

Combination warmers feature tri-temp chamber allowing for 3 different modes of warming, LED display, window doors, and control lock programming.

WarmSafe™
technology



P-2010-S

OVERALL SIZE

16½"W x 25¼"D x 21½"H

COMPARTMENT SIZE

- 2.3 cubic ft.
- 13¼"W x 21¾"D x 14"H

• **Temp Range:**

- Blankets: 98°F - 200°F

• **Total Capacity:**

- 5 - 7 blankets

• Solid door

• Caster (Option)



P-2012

OVERALL SIZE

18½"W x 22"D x 22"H

COMPARTMENT SIZE

- 2.5 cubic ft.
- 15½"W x 18½"D x 15"H

• **Temp Range:**

- Blanket: 90°F - 160°F

• **Total Capacity:**

- 4 - 6 blankets

• Caster (Option)

Heated center shelf



P-2022

OVERALL SIZE

18½"W x 22"D x 28"H
18½"W x 23"D x 34½"H (with casters)

COMPARTMENT SIZE

- 3.5 cubic ft.
- 15½"W x 18½"D x 21"H*

* (9 9/16" H above and below the center shelf)

• **Temp Range:**

- Blanket: 90°F - 160°F

• **Total Capacity:**

- 10 - 12 blankets

• Caster (Option)

shown with left door
hidge mount option



P-2032

OVERALL SIZE

24"W x 24½"D x 35½"H
24"W x 25¼"D x 42"H (with casters)

COMPARTMENT SIZE

- 7.5 cubic ft.
- 21"W x 21"D x 28"H

* (13 3/16" H above and below the center shelf)

• **Temp Range:**

- Blanket: 90°F - 160°F

• **Total Capacity:**

- 20 - 25 blankets

• Caster (Option)



shown with bumper option

P-2040

OVERALL SIZE *(without bumper)*

22"W x 34½"D x 72½"H

COMPARTMENT SIZE

- 7.7 cubic ft. upper
- 19"W x 26½"D x 26¾"H
- 7.7 cubic ft. lower
- 19"W x 26¼"D x 26¾"H

- **Temp Range:**
 - Blankets: 98°F - 160°F
 - Irrigation: 90°F - 150°F
- **Total Capacity:**
 - 40-50 blankets or,
 - 72 1-liter bags or,
 - 54 1-liter bottles
- Two compartments, each with individual controls
- 5" casters
- Bumper (Option)

warming cabinets

blanket & fluid

features

Combination fluid and blanket warmers feature LED display, window doors, and control lock programming.

- No fans or lint traps
- Two compartments, each with individual controls



P-2147

OVERALL SIZE

- 30"W x 28½"D x 75"H (caster standard)
- 30"W x 28½"D x 68"H (feet - option)

COMPARTMENT SIZE

- 5.5 cu. ft. fluid compartment
- 26½"W x 23¾"D x 15"H
- 13.25 cu. ft. blanket compartment
- 26½"W x 23¾"D x 36"H

- **tri mode Range:**
 - Blankets: 90°F - 160°F
 - Irrigation: 90°F - 150°F
 - Injection: 90°F - 104°F
- **Total Capacity:**
 - 24-36 1-liter bags or,
 - 30 1-liter bottles
 - 10-14 blankets (upper chamber)
 - 30-40 blankets (lower chamber)
- Separate temperature controls for each compartment (**tri mode** top chamber only)
- 5" casters



P-2150

OVERALL SIZE

- 30"W x 19¾"D x 75"H

COMPARTMENT SIZE

- 3.7 cu. ft. fluid compartment
- 24¼"W x 18"D x 15"H
- 9 cu. ft. blanket compartment
- 24¼"W x 18"D x 36"H

- **tri mode Range:**
 - Blankets: 90°F - 160°F
 - Irrigation: 90°F - 150°F
 - Injection: 90°F - 104°F
- **Total Capacity:**
 - 24 1-liter bags or,
 - 20 1-liter bottles
 - 9-12 blankets (upper chamber)
 - 24-30 blankets (lower chamber)
- Separate temperature controls for each compartment (**tri mode** top chamber only)
- Pass Through (Option)
- Data Logger (Option)



P-2055

OVERALL SIZE

35"W x 29¼"D x 71"H

COMPARTMENT SIZE

- 10.3 cubic ft. upper
- 26½"W x 23¾"D x 28⅜"H
- 10.3 cubic ft. lower
- 26½"W x 23¾"D x 28⅜"H

- Temp Range:
 - Blankets: 98°F - 160°F
- Total Capacity: 60-70 blankets
- One compartment, two separate doors
- Circulation fan for even temperature
- 5" casters

warming cabinets

blanket

features

Elite Series blanket warmers feature windowed door, programmable control with temperature lock and four digit LED display and single pane energy efficient coated glass window door allows inventory observation.

WarmSafe™
technology

Heated center shelf



P-2210

OVERALL SIZE

- 18½"W x 22"D x 22"H

COMPARTMENT SIZE

- 2.5 cubic ft.
- 15½"W x 18¾"D x 15¼"H

- Temp Range:
 - Blankets: 90°F - 160°F
- A warming shut-off system, separate from the electronic control, prevents overheating
- Interior blue lighting



P-2220

OVERALL SIZE

- 18½"W x 22"D x 28"H

COMPARTMENT SIZE

- 3.5 cubic ft.
 - 15½"W x 18¾"D x 21¼"H*
- * (9 9/16"H above & below the center shelf)

- Temp Range:
 - Blankets: 90°F - 160°F
- A warming shut-off system, separate from the electronic control, prevents overheating
- Interior blue lighting



P-2230

OVERALL SIZE

- 24"W x 24½"D x 22"H

COMPARTMENT SIZE

- 4 cubic ft.
- 21"W x 21½"D x 15¼"H

- Temp Range:
 - Blankets: 90°F - 160°F
- A warming shut-off system, separate from the electronic control, prevents overheating
- Interior blue lighting

Heated center shelf



P-2240

OVERALL SIZE

- 24"W x 24¼"D x 35"H

COMPARTMENT SIZE

- 7.5 cubic ft.
 - 21"W x 21¾"D x 28¼"H*
- * (13 1/8"H above & below the center shelf)

- Temp Range:
 - Blankets: 90°F - 160°F
- A warming shut-off system, separate from the electronic control, prevents overheating
- Interior blue lighting



P-2112

OVERALL SIZE

18½"W x 23½"D x 22"H

COMPARTMENT SIZE

- 2.5 cubic ft.
- 15½"W x 18¾"D x 15¼"H

- Temp Range:
 - Irrigation: 90°F - 150°F
 - Injection: 90°F - 104°F
- Total Capacity:
 - 16 1-liter bags or
 - 12 1-liter bottles
- Glide out basket
- Casters (option)



P-2122

OVERALL SIZE

18½"W x 23½"D x 28"H

COMPARTMENT SIZE

- 3.5 cubic ft.
- 15½"W x 18¾"D x 21¼"H

- Temp Range:
 - Irrigation: 90°F - 150°F
 - Injection: 90°F - 104°F
- Total Capacity:
 - 24 1-liter bags or
 - 24 1-liter bottles
- Glide out basket
- Casters (option)

warming cabinets

fluid

features

Fluid warmers feature 4 digit LED display, window doors, programmable temperature control and interior lighting.



P-2030-TC

OVERALL SIZE

26"W x 33"D x 28"H

features

- Stainless steel
- 4" stainless steel casters with brakes
- 400 lbs. total weight capacity at 200 lbs. per shelf
- Top shelf
- Bottom shelf with 4-sided rail.
- Compatible with the P-2032, P-2230 and P-2240 warming cabinets

shown with the P-2010-S warmer



P-2010-TC

OVERALL SIZE

23¼"W x 32¼"D x 43"H

features

- Stainless steel
- 4" casters with brake & swivel lock
- 300 lbs. total weight capacity at 100 lbs. per shelf
- Shelf Dimensions 17"W x 27"D x 12¼"H
- Compatible with the P-2010-S warming cabinet



P-2010-CB

OVERALL SIZE

21¼"W x 29¾"D x 6¹³/₁₆"H

features

- Platform
- 4" stainless steel casters with brakes
- 350 lbs. total weight capacity
- Perimeter bumper
- Cutouts in platform capture warming cabinet feet.
- Compatible with the P-2010-S warming cabinet

warming cabinet features



Fluid Warmers

- **WarmSafe™ Technology**
- Safety coated interior
- Fully insulated
- 120 VAC
- Heavy duty hardware
- Glass door
- Perimeter bumper (P-2130 only)

Safety Features

- Built-in speaker for audible feedback
- Safety override feature prevents overheating
- Lockout feature

Options

- Optional left hand door swing available
- Option of casters or fixed legs

Warranty

- One Year Service
- Three Years on Parts
- Lifetime Technical Support



Models

- P-2112
 - P-2122
 - P-2130
 - P-2140*
- * combination fluid/blanket warmer



Blanket Warmers

- **WarmSafe™ Technology**
- Safety coated interior
- Fully insulated
- 120 VAC
- Heavy duty hardware
- Glass door (P-2010-S solid door)

Safety Features

- Built-in speaker for audible feedback
- Safety override feature prevents overheating
- Lockout feature

Options

- Optional left hand door swing available
- Option of casters or fixed legs
- Perimeter bumper is optional (excludes P-2055)

Warranty

- One Year Service
- Three Years on Parts
- Lifetime Technical Support



Models

- P-2010-S
- P-2012
- P-2022
- P-2032
- P-2040
- P-2055
- P-2210
- P-2220
- P-2230
- P-2240

tri mode

Blanket & Fluid Warmers

- **WarmSafe™ Technology**
- **tri mode**
- Safety coated interior
- Fully insulated
- 120 VAC
- Heavy duty hardware
- Glass or solid door

Safety Features

- Built-in speaker for audible feedback
- Safety override feature prevents overheating (Deluxe models only)
- Lockout feature (Deluxe models only)

Options

- Optional left hand door swing available
- Option of casters or fixed legs (excludes P-2150)
- Optional pass through warmer (P-2150 only).

Warranty

- One Year Service
- Three Years on Parts
- Lifetime Technical Support



Models

- P-2147
- P-2150
- P-2420
- P-2430



ivNow

individual warming pods

Modular Configuration

Wall mount:

One to six (1-3) bag capacity

Countertop:

One to three (1-3) bag capacity

Pole mount:

One to three (1-3) bag capacity

Temperature:

- Heats to 104°F (40°C) in 30 minutes or less (slightly longer heating time is required for 3L bags)
- Accuracy of +0°/-2°C (+0°/-3°F)

Electronic Control

Monitors the length of time the bag has been held at temperature, displayed additionally by a status button. The control alerts users when a fluid bag has been held at temperature longer than 14 days.

Warranty

1 year parts and labor



features

The ivNow® fluid warmer quickly warms and maintains the temperature of injection/intravenous and irrigation solutions prior to their use. The specially contoured warming module cradles solution bags in 0.5-, 1-, 2- & 3-liter sizes. ivNow® units can be customized in the field by stacking or removing pods from the configuration. Units can be used for countertop use or wall mounted with the provided mounting plate.



ivNow-1

The ivNow-1 may be placed directly on the countertop or fitted with an optional bracket for mounting on a stand or wall.

P-2301-A

Mount

- Equipment pole stand
- Wall mounting brackets

Capacity

One (1) bag, up to 3l *



ivNow-2

The ivNow-2 may be placed directly on the countertop or fitted with an bracket for mounting on a stand or wall.

P-2302-A

Mount

- Equipment pole stand
- Wall mounting brackets

Capacity

Two (2) bags, up to 3l *



ivNow-3

The ivNow-3 may be placed directly on the countertop or fitted with an bracket for mounting on a stand or wall.

P-2303-A

Mount

- Equipment pole stand
- Wall mounting brackets

Capacity

Three (3) bags, up to 3l *