

DD-PAD - ABI Kit with Doppler



Primary Care



Podiatry



Wound Care



Single-Level

CLINIC PLACEMENT

EXAMS PERFORMED



American-Made Quality



Includes labor, parts, and accidental breakage

Newman Medical's DD-PAD is designed to quickly and easily produce the results you need for the diagnosis of lower extremity peripheral artery disease. All of our vascular ABI systems are Made in the USA and have an industry-leading 2 year warranty.

DD-PAD Exams

- Single-Level

DD-PAD Includes:

- Manual Aneroid
 - 1 x 10cm EZ-Clean Vasocuffs
 - 1 x 12cm EZ-Clean Vasocuffs
- Carry Bag
- Two-Year Warranty
 - Includes all parts, labor, and accidental breakage



simpleABI Vascular Systems: Quality You Can Trust

Made in the USA

- High-quality components, manufactured in Colorado.
- Durable design for busy clinical settings.
- 2-year warranty with complete coverage.



Newman Medical: Your Partner in Vascular Care

- Leaders in ultrasound diagnostics since the 1970s.
- Committed to innovation and providing exceptional vascular products.
- Focused on service and long-term customer relationships.

First-Class Support

- Experienced customer service team with extensive industry knowledge.
- Dedicated field representatives for personalized assistance.
- Comprehensive clinical support resources, both online and in-person.

DD-PAD



Exams Performed



Single-Level

Ordering Information

System

SKU	DESCRIPTION
DD-PAD	ABI Kit with 8MHz Doppler

Accessories

SKU	DESCRIPTION
ACC-200	Set of 8 Cuff-Link Tubing
ACC-210	Set of 4 Cuff-Link Tubing
PUMP-100	Manual cuff inflator

Replacement Cuffs

SKU	DESCRIPTION
CUFF-200	EZ Clean Vascular Cuff, 10cm (ankle, small arm)
CUFF-210	EZ Clean Vascular Cuff, 12cm (arm, ankle, calf)
CUFF-210L	EZ Clean Vascular Cuff, 12cm long (above knee)
CUFF-SET-242	EZ Clean Vascular Cuff Set - 2x10cm, 4x12cm, 2x12cm - 8/pk



DD-PAD Technical Specifications

Weight: 3.6 kgs (8 pounds)

Level of Protection against electrical shock: Type B Applied Part, Class II Equipment

Comply with the following Standards: IEC60101-1, IEC60601-2, IEC60601-2-37

Operating Temperature: 10° ~ 40°C (50° ~ 104°F)

Operating Humidity: 30% ~ 75%

Transport/Storage Temperature: -20° ~ 50°C (-4° ~ 122°F)

Transport/Storage Humidity: 5% ~ 90%, non-condensing

Battery Life: 800, 1 minute exams

GTIN: 00852785008524

