

GSF / Low Profile Magnetic Stirrer



GSF Low Profile Magnetic Stirrer

The GSF Low Profile Magnetic Stirrer is an ideal choice for most basic stirring applications. With a height of only 15mm (0.6 inches), the GSF can be stored virtually anywhere and is easily transported. An automated reverse motion setting provides additional agitation as needed.

Features:

- Single direction (stir) and auto-reverse (mix) functionality
- Variable speed range from 15 to 1000rpm
- Used for various mixing applications
- Includes all power adaptors (universal voltage)
- PET surface for high chemical resistance
- Virtually silent operation
- cTUVus approved for UL and CSA
- Spill resistant chassis

*For simple, robust stirring, choose the
Globe Scientific GSF!*

Low Profile Magnetic Stirrer



Specifications	GSE
Working Area	90mm (3.5 inches)
Maximum Volume	0.8L (H ₂ O)
Magnetic Bar Length	40mm (1.6 inches)
Voltage	110-120V/220-230V, 50/60Hz
Motor Output Power	3W
Power	5W
Motor Type	Motorless
Speed Range	15 - 1000rpm
Spill Protection	IP65
Dimensions (WxDxH)	175 x 120 x 15mm (6.9 x 4.7 x 0.6 in)
Weight	0.3kg (0.7 lbs)
Operating Temperature	5° - 40° C
Permissible Relative Humidity	80% RH (non-condensing)
Warranty	2 Years

ORDERING INFORMATION

Item #	Description	Unit
GSF	Magnetic Stirrer, 100-240v, 50/60Hz, with US, UK and EU plugs	Each

