



Removable Rotors

The TrueBond Duet includes two quick swap rotors, allowing a seamless transition between a 2-place fixed angle rotor (left) for 1.5-2 mL blood or urine tubes, to a 12-place 40 mm microhematocrit rotor (right).

TRUEBOND DUET

COMPACT DUAL-ROTOR CENTRIFUGE

Part # 00-056-009-000

The TrueBond Duet is Drucker Diagnostics' most compact animal health centrifuge, designed to spin microhematocrit tubes, blood, and urine all in one unit. Its removable rotors allow you to handle a wide variety of veterinary samples with ease.

Easy to Use

The simple two-button interface makes it easy to select a cycle. Use all five presets for routine veterinary testing, or lock to a single cycle for maximum repeatability.

Compact Size

Weighing only 5.7 lbs (2.6 kg) and measuring 7 x 7 x 7 in (17.8 x 17.8 x 17.8 cm), the TrueBond Duet is our smallest veterinary centrifuge.

Safe and Durable

The TrueBond Duet's auto-pop lid locks securely during a run, and pops open automatically when the cycle is done. The brushless motor, reinforced carbon fiber components, and two-year calibration guarantee ensure years of operation with no routine maintenance.

A Great Value

The TrueBond Duet includes an easily swappable fixed angle rotor, microhematocrit rotor, microhematocrit reader card, and a 2-year warranty in the affordable price.

Microtube Rotor Compatibility

The TrueBond Duet's 2-place, fixed angle Microtube Rotor is designed to fit most standard microtubes from leading suppliers, including BD, Greiner, Sarstedt, and more. Microtubes designed for use with 13 x 75 mm clinical adapters may not be compatible. We recommend verifying tube fit prior to purchase to ensure compatibility.

Applications	Max Speed	Max Capacity	Included	Warranty
Microhematocrit, Urine, Blood	15800 Max RPM 12000 xg Max RCF (1.5 - 2 mL) 13700 xg Max RCF (Microhematocrit)	2 x 1.5 - 2 mL Blood or Urine Tubes 12 x 40mm Microhematocrit Tubes	Fixed Angle Rotor Microhematocrit Rotor Microhematocrit Reader Card	2 years Extended warranty options available

TrueBond Duet



Free 30-Day Evaluation (U.S. Only)



Standard Preset Cycles	Time	RPM	Fixed Angle Rotor (1.5-2 mL)	MHCT Rotor (Microhematocrit)
Cycle 1 (Quick)	30 sec	15800	12000 xg	N/A
Cycle 2 (Normal)	1.5 min	15800	12000 xg	N/A
Cycle 3 (Long)	2.5 min	15800	12000 xg	N/A
Cycle 4 (Urine)	45 sec	9800	3900 xg	N/A
Cycle 5 (Microhematocrit)	2 min	15800	N/A	13700 xg

Part Numbers

Part Numbers		
Centrifuge	00-056-009-000	
Included	2-Place Fixed Angle Rotor	02-001-0-0029
	12-Place Microhematocrit Rotor	02-001-0-0030
	Veterinary Microhematocrit Reader Card	03-1-0012-0232
	1 Year Extended Warranty	03-0-0007-0001
Optional	2 Year Extended Warranty	03-0-0007-0002
	3 Year Extended Warranty	03-0-0007-0006

Specifications

Max RPM	15800 RPM
Max G-Force (1.5 - 2 mL)	12000 xg
Max G-Force (Microhematocrit)	13700 xg
Dimensions (W x D x H)	7 x 7 x 7 in 17.8 x 17.8 x 17.8 cm
Weight	5.7 lbs (2.6 kg)
Power	100 - 240 (+/- 10%) VAC - 50/60 Hz

