

Technical Data Sheet

Rev. 14252

Page 1 of 2

5mL CryoClear[™] Sterile, Barcoded Cryogenic Vials

Item# 3008 - Internal thread, round bottom, self-standing











Item# 3008 (shown actual size)

All CryoClear™ cryogenic vials are sold in tamper evident, resealable plastic bags. 50 vials per bag, 10 bags per case.

Description

Globe Scientific's CryoClear™ vials are designed for cryogenic storage and transport of biological specimens at temperatures as low as -196°C. This innovative line features outstanding leak resistance and purity due to the special thermoplastic elastomer layer that is co-molded with the screw cap. The caps feature a star shaped top cavity that is engineered to work with automated capping/decapping equipment. Each vial has a unique printed barcode for automated data collection, accurate sample inventory, and to conceal the sample's identity. The vials have printed graduation marks for exact measurements and a large white writing area for manual specimen identification.

Features and Benefits

- Screw caps are molded with a thermoplastic elastomer (TPE) layer to provide a 100% leak-proof seal
- Star shaped top cavity is engineered for use with automated capping/decapping equipment
- Unique barcode printed on each vial for automated data collection
- White writing surface for specimen identification
- Printed graduations for accurate measurements
- Vials and caps are autoclavable
- Produced from medical grade raw materials that will not discolor after re-sterilizing
- Chemical resistant polypropylene vial
- Tamper evident packaging
- Self-standing vials interlock in Globe workstation

Products

| Item# | Description | Packaging |
|-------|--------------------------------|--------------|
| 3008 | 5mL, sterile cryogenic vial, | 50 per bag, |
| | internal thread, round bottom, | 500 per case |
| | self-standing | |

Technical Data Sheet

Rev. 14252

Page 2 of 2

5mL CryoClear[™] Sterile, Barcoded Cryogenic Vials

Item# 3008 - Internal thread, round bottom, self-standing

Technical Specifications

Material: Vial: Medical/FDA Polypropylene (PP)

Cap: Medical/FDA Polyethylene (PE) co-molded with a

thermoplastic elastomer (TPE) layer

Sterilization: Beta radiation

SAL level: 10-6

Autoclavable: Vials and caps Temperature range: -196° to +121°C

Mold release agents: None used in manufacturing

Maximum psi: 14.5 psi

Maximum centrifugation speed: 17530 xg (To obtain RPM, verify the diameter of the

centrifuge and convert)


Printing on the vials is resistant to the following common laboratory chemicals:

Isopropyl alcohol: 5-100% Butanol: 100% DMS0: 10-20% Bleach: 5% Acetic acid: 10%

Hydrochloric acids: 10%

NaOH: 10%

| 5mL - Internal Thread | | | |
|-----------------------|----------------|--------|--|
| Α | Overall Height | 90.5mm | |
| В | Vial Height | 82.4mm | |
| С | Cap Height | 8.3mm | |
| D | Cap O.D. | 12.3mm | |
| Е | Vial I.D. | 10.0mm | |
| F | Vial O.D. | 12.5mm | |



Product Certifications

Manufacturing environment: Produced, assembled and packaged in a ISO 7 cleanroom (Class 10,000) in accordance with quality quidelines ISO 13485:2004,

ISO 14644, ISO 14698 (Federal Standard 209), ISO 14000 and ISO 18000

Material: Virgin raw materials are tested according to the "United States Pharmacopia" (USP) and with the "drug master file" (DMF) at the FDA Certified

under USP Class VI

CONEG: This product meets CONEG requirements and therefore does not contain heavy metals in the color concentrate

Sterilization: Sterilzed in accordance with EN ISO 11137

DNase, RNase and pyrogen free: Every lot is certified* by an independent laboratory to be free of DNase, RNase and pyrogens

Human DNA and ATP free: Every lot is certified* by an independent laboratory to be free of Human DNA and ATP

Non-cytotoxic: This product is certified* to be free of cytotoxins

Non-hemolytic: This product is certified* to be free of articles causing hemolysis

In vitro Diagnostic Medical Device: Complies with Directive 98/79/EC of the European Parliament and the Council of 27 October 1998 on in vitro diagnostic medical devices

Leak proof: Vials are certified leak proof at a pressure of 95 kPa (0.95 bar, 14.5 psi) by applying a closure force of not less than 8 cNm

IATA (International Air Can be used as a primary receptacle for the transport of diagnostic specimens as outlined by the IATA Dangerous Goods Regulations,

Transportation Association): Part 6.3,5

*Certificate of Analysis available upon request.

