

## ENERGY EFFICIENT MODEL VSU80-30

### UPRIGHT ULTRA LOW FREEZER -40°C TO -80°C

<b>Capacity [ Cu. Ft. ]</b>	<b>30 Cu. Ft.</b>
<b>Capacity [ Liters ]</b>	<b>877 Liters</b>
<b>Temperature Range [ °C ]</b>	<b>-40°C to -80°C</b>
<b>Temperature Range [ °F ]</b>	<b>-40°F to -112°F</b>

IMAGE BELOW DOES NOT SHOW OPTIONAL ACCESSORIES

Dimensions	Width x Depth x Height
Exterior [ Inches ]	59.25" x 37" x 79.5"
Interior [ Inches ]	42" x 25" x 51.25"
Exterior [ Centimeters ]	150 x 93 x 201
Interior [ Centimeters ]	106 x 63 x 130
Refrigeration System	Cascade-Style System
Compressors	2, Variable Speed
Air Circulation	Gravity Flow
Defrost Method	Manual
Refrigerant	HCFC & CFC Free
Exterior	Powder Coated Steel
Interior	Zinc Coated Galvanized Steel
Insulation	Polyurethane (Ecomate) Foam
Inner Doors	5, Stainless Steel
Lockable Door	Lockable with Padlock
Porthole	Optional 1/2"
Casters	10, Swivel with Locks
Storage Shelves	5 Fixed Shelves
Shipping Weight	1325 Lbs.



#### Electrical

Standard Voltage	115 Volts, 60 Hertz, 1 Phase
Amps / Run Amps / Plug	15A   7.5A   NEMA 5-15
( Optional Voltages )	208 Volts, 230 Volts
Certification(s)	ETL Listed

#### Controller

Display Type	Microprocessor, Digital
Touchscreen	Yes, 4.3" Color Display
Alarms	High/Low Temperature
Alarm Notification	Yes, Audible, Email, Text
Data Logging	Yes, Adjustable Intervals
Data Download	Yes, via USB, CSV Format
LAN Remote Access	Yes, via VNC
Min / Max Temperature	Yes, Display and Reset
Alarm Relay	Yes, Dry Contacts
Automatic Restart	Yes, After Power Failure



**Warranty** 1 Year Parts & Labor