

## MODEL C40-5

### CHEST ULTRA LOW FREEZER 0°C TO -40°C

<b>Capacity [ Cu. Ft. ]</b>	<b>5 Cu. Ft.</b>
<b>Capacity [ Liters ]</b>	<b>142 Liters</b>
<b>Temperature Range [ °C ]</b>	<b>0°C to -40°C</b>
<b>Temperature Range [ °F ]</b>	<b>32°F to -40°F</b>
Dimensions	Width x Depth x Height
Exterior [ Inches ]	40.5" x 31" x 43.75"
Interior [ Inches ]	30" x 18" x 16"
Exterior [ Centimeters ]	102 x 81 x 111
Interior [ Centimeters ]	76 x 46 x 40
Refrigeration System	Single Stage System
Compressors	1, Hermetic Compressor
Air Circulation	Gravity Flow
Defrost Method	Manual
Refrigerant	HCFC & CFC Free
Exterior	Powder Coated Steel
Interior	Zinc Coated Galvanized Steel
Insulation	Polyurethane (Ecomate) Foam
Additional Insulation	Beaded Foam Sub-Lids
Lockable Lid	Lockable with Padlock
Porthole	Optional 1/2"
Casters	4, Swivel with Locks
Storage	Optional Inventory Racks
Shipping Weight	525 Lbs.

<b>Electrical</b>	
Standard Voltage	115 Volts, 60 Hertz, 1 Phase
Amps / Run Amps / Plug ( Optional Voltages )	15A   6A   NEMA 5-15 208 Volts, 230 Volts
Certification(s)	ETL Listed

<b>Controller</b>	
Display Type	Microprocessor, Digital
Alarms	High/Low Temp, Power Failure, Low Battery
Alarm Relay	Yes, Dry Contacts
Automatic Restart	Yes, Automatically Restarts After Power Failure
Backup Battery	Yes, Only Powers Alarm

IMAGE BELOW DOES NOT SHOW OPTIONAL ACCESSORIES



**Warranty** 1 Year Parts & Labor