

MODEL C40-21

CHEST ULTRA LOW FREEZER 0°C TO -40°C

| | |
|---------------------------------|------------------------------|
| Capacity [Cu. Ft.] | 21 Cu. Ft. |
| Capacity [Liters] | 594 Liters |
| Temperature Range [°C] | 0°C to -40°C |
| Temperature Range [°F] | 32°F to -40°F |
| Dimensions | Width x Depth x Height |
| Exterior [Inches] | 91" x 36" x 49" |
| Interior [Inches] | 81" x 21.5" x 21" |
| Exterior [Centimeters] | 231 x 91 x 124 |
| Interior [Centimeters] | 205 x 54 x 53 |
| Refrigeration System | Single Stage System |
| Compressors | 1, Hermetic Compressor |
| Air Circulation | Gravity Flow |
| Defrost Method | Manual |
| Refrigerant | HCFC & CFC Free |
| Exterior | Powder Coated Steel |
| Interior | Zinc Coated Galvanized Steel |
| Insulation | Polyurethane (Ecomate) Foam |
| Additional Insulation | Beaded Foam Sub-Lids |
| Lockable Lid | Lockable with Padlock |
| Porthole | Optional 1/2" |
| Casters | 8, Swivel with Locks |
| Storage | Optional Inventory Racks |
| Shipping Weight | 1025 Lbs. |

Electrical

| | |
|---|--|
| Standard Voltage | 115 Volts, 60 Hertz, 1 Phase |
| Amps / Run Amps / Plug (Optional Voltages) | 20A 7.3A NEMA 5-20 208 Volts, 230 Volts |
| Certification(s) | ETL Listed |

Controller

| | |
|-------------------|--|
| Display Type | Microprocessor, Digital |
| Alarms | High/Low Temp, Power Failure, Low Battery |
| Alarm Relay | Yes, Dry Contacts |
| Automatic Restart | Yes, Automatically Restarts After Power Failure |
| Backup Battery | Yes, Only Powers Alarm |

IMAGE BELOW DOES NOT SHOW OPTIONAL ACCESSORIES



Warranty 1 Year Parts & Labor