

MODEL C40-14X

EXPLOSION PROOF CHEST FREEZER 0°C TO -40°C

Capacity [Cu. Ft.]	14 Cu. Ft.
Capacity [Liters]	400 Liters
Temperature Range [°C]	0°C to -40°C
Temperature Range [°F]	32°F to -40°F

Dimensions	Width x Depth x Height
Exterior [Inches]	72.5" x 37" x 47.5"
Interior [Inches]	62" x 20" x 20"
Exterior [Centimeters]	184 x 93 x 120
Interior [Centimeters]	157 x 50 x 50
Refrigeration System	Single Stage System
Compressors	1, Hermetic Compressor
Compressor Container	Explosion Proof
Air Circulation	Gravity Flow
Defrost Method	Manual
Refrigerant	HCFC & CFC Free
Exterior	Powder Coated Steel
Interior	Zinc Coated Galvanized Steel
Insulation	Polyurethane (Ecomate) Foam
Additional Insulation	Beaded Foam Sub-Lids
Lockable Lid	Lockable with Padlock
Casters	6, Swivel with Locks
Storage	Optional Inventory Racks
Shipping Weight	900 Lbs.

Electrical	
Standard Voltage	115 Volts, 60 Hertz, 1 Phase
Amps / Run Amps / Plug (Optional Voltages)	20A 7.3A NEMA 5-20 208 Volts, 230 Volts
Power Configuration	Hardwired
Certification(s)	UL Rated
Certification File Number	SA10711
Certification Classification	Class I, Division I & II, Groups C & D

Controller	
Display Type	Explosion Proof, Digital

Warranty 1 Year Parts & Labor

IMAGE BELOW DOES NOT SHOW OPTIONAL ACCESSORIES

