

## MODEL U40-28

### UPRIGHT ULTRA LOW FREEZER 0°C TO -40°C

<b>Capacity [ Cu. Ft. ]</b>	<b>28 Cu. Ft.</b>
<b>Capacity [ Liters ]</b>	<b>792 Liters</b>
<b>Temperature Range [ °C ]</b>	<b>0°C to -40°C</b>
<b>Temperature Range [ °F ]</b>	<b>32°F to -40°F</b>

IMAGE BELOW DOES NOT SHOW OPTIONAL ACCESSORIES

Dimensions	Width x Depth x Height
Exterior [ Inches ]	54" x 37" x 79.5"
Interior [ Inches ]	38" x 25" x 51.25"
Exterior [ Centimeters ]	137 x 93 x 201
Interior [ Centimeters ]	96 x 93 x 130
Refrigeration System	Single Stage System
Compressors	1, Hermetic Compressor
Air Circulation	Gravity Flow
Defrost Method	Manual
Refrigerant	HCFC & CFC Free
Exterior	Powder Coated Steel
Interior	Zinc Coated Galvanized Steel
Insulation	Polyurethane (Ecomate) Foam
Inner Doors	5, Stainless Steel
Lockable Door	Lockable with Padlock
Porthole	Optional 1/2"
Casters	6, Swivel with Locks
Storage	4 Adjustable Shelves, with 1 Base Shelf
Shipping Weight	1300 Lbs.



<b>Electrical</b>	
Standard Voltage	115 Volts, 60 Hertz, 1 Phase
Amps / Run Amps / Plug ( Optional Voltages )	20A   7.3A   NEMA 5-20 208 Volts, 230 Volts
Certification(s)	ETL Listed

<b>Controller</b>	
Display Type	Microprocessor, Digital
Alarms	High/Low Temp, Power Failure, Low Battery
Alarm Relay	Yes, Dry Contacts
Automatic Restart	Yes, Automatically Restarts After Power Failure
Backup Battery	Yes, Only Powers Alarm



**Warranty** 1 Year Parts & Labor