

MODEL U40-22X

EXPLOSION PROOF UPRIGHT FREEZER 0°C TO -40°C

Capacity [Cu. Ft.]	22 Cu. Ft.
Capacity [Liters]	626 Liters
Temperature Range [°C]	0°C to -40°C
Temperature Range [°F]	32°F to -40°F
Dimensions	Width x Depth x Height
Exterior [Inches]	47.25" x 37" x 79.5"
Interior [Inches]	28.5" x 26" x 51.25"
Exterior [Centimeters]	120 x 93 x 201
Interior [Centimeters]	72 x 66 x 130
Refrigeration System	Single Stage System
Compressors	1, Hermetic Compressor
Compressor Container	Explosion Proof
Air Circulation	Gravity Flow
Defrost Method	Manual
Refrigerant	HCFC & CFC Free
Exterior	Powder Coated Steel
Interior	Zinc Coated Galvanized Steel
Insulation	Polyurethane (Ecomate) Foam
Inner Doors	5, Stainless Steel
Lockable Door	Lockable with Padlock
Casters	4, Swivel with Locks
Storage	4 Adjustable Shelves, with 1 Base Shelf
Shipping Weight	975 Lbs.

Electrical

Standard Voltage	115 Volts, 60 Hertz, 1 Phase
Amps / Run Amps / Plug (Optional Voltages)	20A 7.3A NEMA 5-20 208 Volts, 230 Volts
Power Configuration	Hardwired
Certification(s)	UL Rated
Certification File Number	SA10711
Certification Classification	Class I, Division I & II, Groups C & D

Controller

Display Type	Explosion Proof, Digital
--------------	--------------------------

IMAGE BELOW DOES NOT SHOW OPTIONAL ACCESSORIES



Warranty 1 Year Parts & Labor