

Material Safety Data Sheet
 May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 consulted for specific requirements.

U.S. Department of Labor
Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072



IDENTITY (As Used on Label and List)
 AQUAFLEX® ULTRASOUND GEL PAD

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name PARKER LABORATORIES, INC.	Emergency Telephone Number
Address (Number, Street, City, State and ZIP Code) 286 ELDRIDGE ROAD	Telephone Number for Information (973) 276-9500
FAIRFIELD, NJ 07004	Date Prepared SEPTEMBER 2006
	Signature of Preparer (optional)

Section II – Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
NONE				

Section III – Physical/Chemical Characteristics

Boiling Point	N/A	Specific Gravity (H²O = 1)	1.03
Vapor Pressure (mm Hg.)	N/A	Melting Point	N/D
Vapor Density (AIR = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	N/A
Solubility in Water SOLUBLE			
Appearance and Odor BUFF COLORED, TRANSLUCENT GEL PAD; LITTLE OR NO ODOR			

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) NON-FLAMMABLE	Flammable Limits N/A	LEL N/A	UEL N/A
Extinguishing Media USE EXTINGUISHING MEDIA APPROPRIATE FOR SURROUNDING FIRE.			
Special Fire Fighting Procedures NONE			
Unusual Fire and Explosion Hazards NONE			

