

Ready Warm Workstation

The Ready Warm is a multi-use digital warming plate for clinics, laboratories, and research facilities. Various applications include warming slides, petri dishes and other biological specimens requiring consistent and accurate heat. The Ready Warm can hold 66 glass slides or 15 100mm petri dishes.

The Ready Warm features all stainless steel and aluminum construction with a precision digital temperature controller, and is made in LW Scientific's ISO 13485:2016 certified factory in Atlanta, GA.

CONSTRUCTION

Corrosion resistant aluminum
Durable metal construction

SPECIFICATIONS

Temperature range: Ambient to 122°F +/-5°F
Preset at 100°F (37°C)
Accuracy: +/- 1.8°F
Heating surface: 12" x 18"

WEIGHT AND DIMS

Length: 22.835" (580mm)
Width: 12" (305mm)
Height: 3.07" (78mm)
Weight: 13lbs (5.89kg)

POWER / CONTROLS

Lighted power switch
Auto-switching CE / cUL approved power adapter
Output: 24vDC / 6A
Input: 100-240vAC 50/60Hz

ADVANTAGES

Compact design



Designed, Engineered &
Assembled Proudly in America

Ready Warm: Warm Working Station

Model #	Description
FWL-04PL-BTD3	Ready Warm: Warm Working Station

- Designed, engineered, and assembled in the USA
- Even heat distribution
- Digital temperature readout

